

RESU3.3

Data sheet for RESU3.3



Su proveedor LG .
By. FH Solar & Led **Ibérica** .S.L
Núñez Morgado 5 Madrid 28036
Tel : +34 91323534 +34 6000 27027
info@fhsolarled.com
www.fhsolarled.com
España



RESU3.3

Electrical Characteristics

Total Energy Capacity	3.3 kWh
Usable Energy Capacity ¹⁾	2.9 kWh
Battery Capacity	63 Ah
Voltage Range	42.0 to 58.8 V _{DC}
Nominal Voltage	51.8 V _{DC}
Max. Charge/Discharge Current	71.4A
Peak Current ²⁾	78.6A for 3 sec.
Max. Charge/Discharge Power ³⁾	3.0kW
Peak Power ²⁾	3.3kW for 3 sec.
Battery Pack Round-Trip Efficiency	>95% (under specific condition)
Communication Interface	CAN 2.0B
DC Disconnect	Circuit Breaker, Contactor, Fuse

Operating Conditions

Installation Location	Indoor / Outdoor (Stand / Wall-Mounted)
Operating Temperature	-10 to 45°C
Operating Temperature (Recommended)	15 to 30°C
Storage Temperature	-30 to 60°C : ~7 days -20 to 45°C : ~6 months
Humidity	5% to 95%
Altitude	Max. 2,000m
Cooling Strategy	Natural Convection

Certification

Safety	Cell	UL1642
	Battery Pack	CE / RCM / FCC / TUV (IEC 62619) / UL1973
EMC		IEC61000-6-1, IEC61000-6-3
Hazardous Materials Classification		Class 9
Transportation		UN38.3
Ingress Rating		IP55

※ Test Conditions - Temperature 25°C, at the beginning of life

※ Total Energy is measured under specific condition from LGC(0.3CCCV/0.3CC)

1) Value for Battery Cell Only (Depth of Discharge 90%). Actual usable energy at the AC output may vary by condition, such as the inverter efficiency and temperature.

2) Peak Current excludes repeated short duration (less than 3 sec.) of current pattern.

3) LG Chem recommends 1.1kW for maximum battery lifetime.

Features

RESU3.3 battery pack designed for photovoltaic systems is easily adaptable energy storage solution. With RESU Plus, RESU3.3/6.5/10 can be “cross-connected” with each other.

※ RESU Plus is an expansion kit specially designed for 48V models.
Number of expandable battery units : up to 2EA

- ❑ Easy and Flexible installation
 - : Easy to wall mount or install on floor
 - : Wide range of inverters available
- ❑ Proven Safety and 10 year warranty
- ❑ Compact size and space saving



Mechanical Characteristics

Dimensions	Width	452 mm (17.8")
	Height	401 mm (15.8")
	Depth	120 mm (4.7")
Weight		31 kg (68.3lbs)

